



Bullet 2C 4MP

Model: IPC-F42P/IPC-F42N

4MP H. 265 Bullet Wi-Fi Camera

Bullet 2C 4MP delivers 4MP live monitoring with a choice of 2.8mm/3.6mm/6mm lens option, it supports the latest H.265 compression which can save up to 50% bandwidth and storage. Human Detection allows you to monitor what matters without receiving annoying false alerts. With IP67 certified, the camera can be used outdoors under different weather conditions.



H. 265 4MP QHD

See more than 1080P



Human Detection

Quickly find human targets in you home



Built-in Microphone

High quality microphone picks up sounds clearly while monitoring



H. 265 Codec

Save more high-quality video in less space



IP67

Weatherproof from dust and water



Alarm Notification

Sends instant motion-activated alerts to your mobile phone



Diversified Storage

Supports NVR, Cloud Storage or Micro SD card (up to 256GB)



24/7 Protection

Infrared night vision for clear-as-day clarity even in pitch dark



Wi-Fi Connection

IEEE802.11b/g/n(2.4GHz)



Stay close with what you care

With Cloud service, you will have access to what you care as long as Internet is available. You can record daily or motion videos on Cloud and play back anytime anywhere.



Speci cations

Camera

1/2.7" 4 Megapixel Progressive CMOS

4MP (2560 x 1440)

Night Vision: 30m(98ft) Distance

2.8 mm/3.6 mm/6 mm Fixed Lens

Field of View: 2.8mm; 106° (H), 56° (V), 125° (D)

3.6mm: 92° (H), 48° (V), 109° (D)

6mm: 55° (H), 31° (V), 62° (D)

Video & Audio

 $\label{eq:Video Compression: H. 265/H. 264} Video \ \mbox{Compression: H. 265/H. 264}$

Up to 25/30 fps Frame Rate

16x Digital Zoom

Built-in Mic

Notice Management

Motion Detection
Configurable Region

Human Detection

What's in the box

- 1x Camera
- 1x Quick Start Guide
- 1x Power Adapter

Network

1 x 100Mbps Ethernet Port

Wi-Fi:IEEE802.11b/g/n, Dual Antenna

Imou App: iOS, Android

ONVIF

Auxiliary Interface

Micro SD Card Slot (up to 256GB)

Reset Button

Genera1

DC 12V0.5A Power Supply Power Consumption: <3.5W

Material: Plastic

Working Environment: -30° C~+55° C, Less Than 95%RH

Dimensions: 147.7 \times 74.2 \times 74.2mm (5.8 \times 2.9 \times 2.9inch)

Weight: 240g (0.511b)

CE, FCC, IP67

- 1x Screw Package
- 1x Installation Position Map
- 1x Waterproof Connector

